



SPECIFICATIONS

Electrical
 Current Rating: 2A AC DC
 Voltage Rating: 250V AC, DC
 Operating Temp.: -25°C ~ +85°C
 Contact Resistance: 20mΩ / Max.
 Insulation Resistance: 1000MΩ / Min.

Material
 Terminal Material: Brass/ Tin-plated/ Gold-plated
 Material: Nylon 66, UL 94V-0+GF

Poles	Dimension mm (in.)		Note.
	A	B	
4	2.0	6.0	
6	4.0	8.0	
8	6.0	10.0	
10	8.0	12.0	
12	10.0	14.0	
14	12.0	16.0	
16	14.0	18.0	
18	16.0	20.0	
20	18.0	22.0	
22	20.0	24.0	
24	22.0	26.0	
26	24.0	28.0	
28	26.0	30.0	
30	28.0	32.0	
32	30.0	34.0	
34	32.0	36.0	
40	38.0	42.0	

RoHS Compliant		玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准	BETTY	TOLERANCE 容許公差 .0 ±0.35 .00 ±0.25 ANG. ±	PART NAME 品名
DWG. 製圖	BETTY		JST PHD 2.0mm WAFER 2XXXP DUAL ROW RIGHT ANGLE WHITE INSULATOR ROHS LOW-LEAD
DATE 制表日	2008/08/19	UNIT 單位	PART NO.
		M M	料號 W2103-XXPDRXXWR
		PAGE 張數	
		1 OF 1	
		REV. 版次	
		A	